

API DOCUMENTATION

REST API Quickstart Kit

Authentication, core endpoints, request/response patterns, and rate limits for the Arcline API v3.

Overview

The Arcline REST API provides programmatic access to workflows, triggers, actions, and analytics data within your organization. All requests are made over HTTPS to the base URL below. The API follows RESTful conventions, uses JSON for request and response bodies, and returns standard HTTP status codes.

```
Base URL:  https://api.arcline.io/v3/
Auth:     Bearer token (header: Authorization: Bearer <token>)
Format:   application/json
```

Authentication

All API requests must include a valid API key issued from your Arcline workspace under Settings › API Keys. Keys are scoped to read-only or read-write and can be revoked at any time. Tokens do not expire by default, but workspace administrators may enforce rotation policies.

```
GET /v3/workflows
Authorization: Bearer ak_live_XXXXXXXXXXXXXXXXXXXXXXXXXXXX

Response 200:
{ "data": [ { "id": "wf_01HZ...", "name": "Lead Intake", "status": "active" } ] }
```

Core Endpoints

```
GET /v3/workflows — List all workflows in the workspace
POST /v3/workflows — Create a new workflow
GET /v3/workflows/{id} — Retrieve a workflow by ID
POST /v3/triggers/fire — Manually fire a trigger event
GET /v3/runs — Fetch recent execution history
GET /v3/analytics/summary — Aggregate run and error metrics
```

Rate Limits

The Arcline API enforces rate limits per API key. Standard keys allow 120 requests per minute and 5,000 requests per hour. Exceeding these limits returns HTTP 429 with a Retry-After header. Enterprise plans support higher limits configured at the workspace level.